

- Indoor Unit : Combination of all type of wall and non-wall series (CS-MZ/Z/XZ/MTZ/TZ/TE/E)
- Outdoor Unit : CU-2Z35TBE

Indoor unit capacity Cooling	Total	Cooling Capacity (kW)				Input Power (W)		EER		ANNUAL ENERGY CONSUMPTION (kWh)	Current, 230V (A)	ERP				MOISTURE REMOVAL VOLUME l/h	
		Room A	Room B	Total	min ~ max	Rating	min ~ max	WW	CLASS			Pdesign (kW)	SEER		Annual Consumption (kWh)		
													WW	CLASS			
1 Room	1.6	1.6	1.60		1.60	1.1 ~ 2.3	460	220 ~ 650	3.48	A	230	2.20	-	-	-		1.0
	2.0	2.0	2.00		2.00	1.1 ~ 2.9	570	220 ~ 820	3.51	A	285	2.70	-	-	-		1.3
	2.5	2.5	2.50		2.50	1.1 ~ 3.5	720	220 ~ 1050	3.47	A	360	3.40	-	-	-		1.5
	3.5	3.5	3.50		3.50	1.1 ~ 4.0	1060	220 ~ 1270	3.30	A	530	4.95	-	-	-		2.0
2 Room	1.6 + 1.6	3.2	1.60	1.60	3.20	1.5 ~ 4.0	750	250 ~ 1100	4.27	A	375	3.50	3.20	7.00	A++	160	1.0 + 1.0
	1.6 + 2.0	3.6	1.55	1.95	3.50	1.5 ~ 4.5	820	250 ~ 1200	4.27	A	410	3.85	3.50	7.00	A++	175	1.0 + 1.3
	1.6 + 2.5	4.1	1.35	2.15	3.50	1.5 ~ 4.5	820	250 ~ 1200	4.27	A	410	3.85	3.50	7.00	A++	175	0.9 + 1.4
	1.6 + 3.5	5.1	1.10	2.40	3.50	1.5 ~ 4.5	820	250 ~ 1200	4.27	A	410	3.85	3.50	7.00	A++	175	0.7 + 1.5
	2.0 + 2.0	4.0	1.75	1.75	3.50	1.5 ~ 4.5	820	250 ~ 1200	4.27	A	410	3.85	3.50	7.00	A++	175	1.1 + 1.1
	2.0 + 2.5	4.5	1.55	1.95	3.50	1.5 ~ 4.5	820	250 ~ 1200	4.27	A	410	3.85	3.50	7.00	A++	175	1.0 + 1.3
	2.0 + 3.5	5.5	1.25	2.25	3.50	1.5 ~ 4.5	790	250 ~ 1150	4.43	A	395	3.70	3.50	7.00	A++	175	0.8 + 1.5
	2.5 + 2.5	5.0	1.75	1.75	3.50	1.5 ~ 4.5	790	250 ~ 1150	4.43	A	395	3.70	3.50	7.00	A++	175	1.1 + 1.1
2.5 + 3.5	6.0	1.45	2.05	3.50	1.5 ~ 4.5	790	250 ~ 1150	4.43	A	395	3.70	3.50	7.00	A++	175	0.9 + 1.3	

Indoor unit capacity Heating	Total	Heating Capacity (kW)				Input Power (W)		EER		ANNUAL ENERGY CONSUMPTION (kWh)	Current, 230V (A)	ERP				MOISTURE REMOVAL VOLUME l/h	
		Room A	Room B	Total	min ~ max	Rating	min ~ max	WW	CLASS			Pdesign (kW)	SCOP		Annual Consumption (kWh)		
													WW	CLASS			
1 Room	1.6	1.6	2.60		2.60	0.7 ~ 3.8	790	170 ~ 1210	3.29	A	395	3.65	-	-	-		
	2.0	2.0	3.20		3.20	0.7 ~ 4.8	950	170 ~ 1510	3.37	A	475	4.40	-	-	-		
	2.5	2.5	3.60		3.60	0.7 ~ 5.5	1130	170 ~ 1800	3.19	B	565	5.25	-	-	-		
	3.5	3.5	4.20		4.20	0.7 ~ 5.6	1320	170 ~ 1780	3.18	B	660	6.10	-	-	-		
2 Room	1.6 + 1.6	3.2	2.10	2.10	4.20	1.1 ~ 5.6	1060	210 ~ 1540	3.96	A	530	4.90	3.00	3.80	A	1105	
	1.6 + 2.0	3.6	1.85	2.35	4.20	1.1 ~ 5.6	1060	210 ~ 1540	3.96	A	530	4.90	3.20	3.80	A	1179	
	1.6 + 2.5	4.1	1.65	2.55	4.20	1.1 ~ 5.6	1060	210 ~ 1540	3.96	A	530	4.90	3.20	3.80	A	1179	
	1.6 + 3.5	5.1	1.30	2.90	4.20	1.1 ~ 5.6	1060	210 ~ 1540	3.96	A	530	4.90	3.20	3.80	A	1179	
	2.0 + 2.0	4.0	2.10	2.10	4.20	1.1 ~ 5.6	1060	210 ~ 1540	3.96	A	530	4.90	3.20	3.80	A	1179	
	2.0 + 2.5	4.5	1.85	2.35	4.20	1.1 ~ 5.6	1060	210 ~ 1540	3.96	A	530	4.90	3.20	3.80	A	1179	
	2.0 + 3.5	5.5	1.55	2.65	4.20	1.1 ~ 5.6	1040	210 ~ 1490	4.04	A	520	4.80	3.20	3.80	A	1179	
	2.5 + 2.5	5.0	2.10	2.10	4.20	1.1 ~ 5.6	1040	210 ~ 1490	4.04	A	520	4.80	3.20	3.80	A	1179	
2.5 + 3.5	6.0	1.75	2.45	4.20	1.1 ~ 5.6	1040	210 ~ 1490	4.04	A	520	4.80	3.20	3.80	A	1179		

- Indoor Unit : Combination of all type of wall and non-wall series (CS-MZ/Z/XZ/MTZ/TZ/TE/E)
- Outdoor Unit : CU-2Z41TBE

Indoor unit capacity Cooling		Total	Cooling Capacity (kW)				Input Power (W)		EER		ANNUAL ENERGY CONSUMPTION (kWh)	Current, 230V (A)	ERP				MOISTURE REMOVAL VOLUME l/h
			Room A	Room B	Total	min ~ max	Rating	min ~ max	W/W	CLASS			Pdesign (kW)	SEER		Annual Consumption (kWh)	
														W/W	CLASS		
1 Room	1.6	1.6	1.60		1.60	1.1 ~ 2.3	460	220 ~ 650	3.48	A	230	2.20	-	-	-	-	1.0
	2.0	2.0	2.00		2.00	1.1 ~ 2.9	570	220 ~ 820	3.51	A	285	2.70	-	-	-	-	1.3
	2.5	2.5	2.50		2.50	1.1 ~ 3.5	720	220 ~ 1050	3.47	A	360	3.40	-	-	-	-	1.5
	3.5	3.5	3.50		3.50	1.1 ~ 4.0	1060	220 ~ 1270	3.30	A	530	4.95	-	-	-	-	2.0
2 Room	1.6 + 1.6	3.2	1.60	1.60	3.20	1.5 ~ 4.0	780	250 ~ 1090	4.10	A	390	3.60	3.20	7.00	A++	160	1.0 + 1.0
	1.6 + 2.0	3.6	1.60	2.00	3.60	1.5 ~ 4.5	880	250 ~ 1250	4.09	A	440	4.05	3.60	7.00	A++	180	1.0 + 1.3
	1.6 + 2.5	4.1	1.60	2.50	4.10	1.5 ~ 5.2	1000	250 ~ 1470	4.10	A	500	4.65	4.10	7.00	A++	205	1.0 + 1.5
	1.6 + 3.5	5.1	1.30	2.80	4.10	1.5 ~ 5.2	1000	250 ~ 1470	4.10	A	500	4.65	4.10	7.00	A++	205	0.8 + 1.6
	2.0 + 2.0	4.0	2.00	2.00	4.00	1.5 ~ 5.0	990	250 ~ 1410	4.04	A	495	4.60	4.00	7.00	A++	200	1.3 + 1.3
	2.0 + 2.5	4.5	1.80	2.30	4.10	1.5 ~ 5.2	1000	250 ~ 1470	4.10	A	500	4.65	4.10	7.00	A++	205	1.2 + 1.5
	2.0 + 3.5	5.5	1.50	2.60	4.10	1.5 ~ 5.2	1000	250 ~ 1470	4.10	A	500	4.65	4.10	7.00	A++	205	1.0 + 1.6
	2.5 + 2.5	5.0	2.05	2.05	4.10	1.5 ~ 5.2	1000	250 ~ 1470	4.10	A	500	4.65	4.10	7.00	A++	205	1.3 + 1.3
2.5 + 3.5	6.0	1.70	2.40	4.10	1.5 ~ 5.2	1000	250 ~ 1470	4.10	A	500	4.65	4.10	7.00	A++	205	1.1 + 1.5	

Indoor unit capacity Heating		Total	Heating Capacity (kW)				Input Power (W)		EER		ANNUAL ENERGY CONSUMPTION (kWh)	Current, 230V (A)	ERP				MOISTURE REMOVAL VOLUME l/h
			Room A	Room B	Total	min ~ max	Rating	min ~ max	W/W	CLASS			Pdesign (kW)	SCOP		Annual Consumption (kWh)	
														W/W	CLASS		
1 Room	1.6	1.6	2.60		2.60	0.7 ~ 3.8	790	170 ~ 1210	3.29	A	395	3.65	-	-	-	-	
	2.0	2.0	3.20		3.20	0.7 ~ 4.8	950	170 ~ 1510	3.37	A	475	4.40	-	-	-	-	
	2.5	2.5	3.60		3.60	0.7 ~ 5.5	1130	170 ~ 1800	3.19	B	565	5.25	-	-	-	-	
	3.5	3.5	4.50		4.50	0.7 ~ 6.2	1350	170 ~ 1910	3.33	B	675	6.25	-	-	-	-	
2 Room	1.6 + 1.6	3.2	2.20	2.20	4.40	1.1 ~ 7.0	1140	210 ~ 2010	3.86	A	570	5.25	3.20	3.80	A	1179	
	1.6 + 2.0	3.6	2.05	2.55	4.60	1.1 ~ 7.0	1160	210 ~ 1990	3.97	A	580	5.35	3.50	3.80	A	1289	
	1.6 + 2.5	4.1	1.80	2.80	4.60	1.1 ~ 7.0	1160	210 ~ 1990	3.97	A	580	5.35	3.50	3.80	A	1289	
	1.6 + 3.5	5.1	1.45	3.15	4.60	1.1 ~ 7.0	1160	210 ~ 1990	3.97	A	580	5.35	3.50	3.80	A	1289	
	2.0 + 2.0	4.0	2.30	2.30	4.60	1.1 ~ 7.0	1150	210 ~ 1970	4.00	A	575	5.30	3.50	3.80	A	1289	
	2.0 + 2.5	4.5	2.05	2.55	4.60	1.1 ~ 7.0	1150	210 ~ 1970	4.00	A	575	5.30	3.50	3.80	A	1289	
	2.0 + 3.5	5.5	1.65	2.95	4.60	1.1 ~ 7.0	1150	210 ~ 1970	4.00	A	575	5.30	3.50	3.80	A	1289	
	2.5 + 2.5	5.0	2.30	2.30	4.60	1.1 ~ 7.0	1150	210 ~ 1970	4.00	A	575	5.30	3.50	3.80	A	1289	
2.5 + 3.5	6.0	1.90	2.70	4.60	1.1 ~ 7.0	1150	210 ~ 1970	4.00	A	575	5.30	3.50	3.80	A	1289		

- Indoor Unit : Combination of all type of wall and non-wall series (CS-MZ/Z/XZ/MTZ/TZ/TE/E)
- Outdoor Unit : CU-2Z50TBE

Indoor unit capacity Cooling	Total	Cooling Capacity (kW)				Input Power (W)		EER		ANNUAL ENERGY CONSUMPTION (kWh)	Current, 230V (A)	ERP				MOISTURE REMOVAL VOLUME l/h	
		Room A	Room B	Total	min ~ max	Rating	min ~ max	WW	CLASS			Pdesign (kW)	SEER		Annual Consumption (kWh)		
													WW	CLASS			
1 Room	1.6	1.6	1.60		1.60	1.1 ~ 2.3	460	220 ~ 650	3.48	A	230	2.20	-	-	-	-	1.0
	2.0	2.0	2.00		2.00	1.1 ~ 2.9	570	220 ~ 820	3.51	A	285	2.70	-	-	-	-	1.3
	2.5	2.5	2.50		2.50	1.1 ~ 3.5	720	220 ~ 1050	3.47	A	360	3.40	-	-	-	-	1.5
	3.5	3.5	3.50		3.50	1.1 ~ 4.0	1060	220 ~ 1270	3.30	A	530	4.95	-	-	-	-	2.0
	4.2	4.2	4.20		4.20	1.1 ~ 4.5	1410	220 ~ 1550	2.98	B	705	6.60	-	-	-	-	2.4
	5.0	5.0	5.00		5.00	1.2 ~ 5.1	1740	230 ~ 1840	2.87	C	870	8.05	-	-	-	-	2.7
2 Room	1.6 + 1.6	3.2	1.60	1.60	3.20	1.5 ~ 4.0	780	250 ~ 1090	4.10	A	390	3.60	3.20	7.00	A++	160	1.0 + 1.0
	1.6 + 2.0	3.6	1.60	2.00	3.60	1.5 ~ 4.5	880	250 ~ 1250	4.09	A	440	4.05	3.60	7.00	A++	180	1.0 + 1.3
	1.6 + 2.5	4.1	1.60	2.50	4.10	1.5 ~ 5.2	1000	250 ~ 1470	4.10	A	500	4.65	4.10	7.00	A++	205	1.0 + 1.5
	1.6 + 3.5	5.1	1.55	3.45	5.00	1.5 ~ 5.2	1280	250 ~ 1470	3.91	A	640	5.80	5.00	7.00	A++	250	1.0 + 2.0
	1.6 + 4.2	5.8	1.40	3.60	5.00	1.5 ~ 5.4	1280	250 ~ 1590	3.91	A	640	5.80	5.00	7.00	A++	250	0.9 + 2.1
	1.6 + 5.0	6.6	1.20	3.80	5.00	1.5 ~ 5.4	1280	250 ~ 1590	3.91	A	640	5.80	5.00	7.00	A++	250	0.7 + 2.2
	2.0 + 2.0	4.0	2.00	2.00	4.00	1.5 ~ 5.0	990	250 ~ 1410	4.04	A	495	4.60	4.00	7.00	A++	200	1.3 + 1.3
	2.0 + 2.5	4.5	2.00	2.50	4.50	1.5 ~ 5.2	1130	250 ~ 1470	3.98	A	565	5.10	4.50	7.00	A++	225	1.3 + 1.5
	2.0 + 3.5	5.5	1.80	3.20	5.00	1.5 ~ 5.4	1280	250 ~ 1590	3.91	A	640	5.80	5.00	7.00	A++	250	1.2 + 1.8
	2.0 + 4.2	6.2	1.60	3.40	5.00	1.5 ~ 5.4	1280	250 ~ 1590	3.91	A	640	5.80	5.00	7.00	A++	250	1.0 + 1.9
	2.0 + 5.0	7.0	1.45	3.55	5.00	1.5 ~ 5.4	1280	250 ~ 1590	3.91	A	640	5.80	5.00	7.00	A++	250	0.9 + 2.1
	2.5 + 2.5	5.0	2.50	2.50	5.00	1.5 ~ 5.4	1280	250 ~ 1590	3.91	A	640	5.80	5.00	7.00	A++	250	1.5 + 1.5
	2.5 + 3.5	6.0	2.10	2.90	5.00	1.5 ~ 5.4	1280	250 ~ 1590	3.91	A	640	5.80	5.00	7.00	A++	250	1.4 + 1.7
	2.5 + 4.2	6.7	1.85	3.15	5.00	1.5 ~ 5.4	1280	250 ~ 1590	3.91	A	640	5.80	5.00	7.00	A++	250	1.2 + 1.8
	2.5 + 5.0	7.5	1.65	3.35	5.00	1.5 ~ 5.4	1280	250 ~ 1590	3.91	A	640	5.80	5.00	7.00	A++	250	1.1 + 1.9
3.5 + 3.5	7.0	2.50	2.50	5.00	1.5 ~ 5.4	1280	250 ~ 1590	3.91	A	640	5.80	5.00	7.00	A++	250	1.5 + 1.5	
3.5 + 4.2	7.7	2.25	2.75	5.00	1.5 ~ 5.4	1280	250 ~ 1590	3.91	A	640	5.80	5.00	7.00	A++	250	1.5 + 1.6	

Indoor unit capacity Heating	Total	Heating Capacity (kW)				Input Power (W)		EER		ANNUAL ENERGY CONSUMPTION (kWh)	Current, 230V (A)	ERP				MOISTURE REMOVAL VOLUME l/h	
		Room A	Room B	Total	min ~ max	Rating	min ~ max	WW	CLASS			Pdesign (kW)	SCOP		Annual Consumption (kWh)		
													WW	CLASS			
1 Room	1.6	1.6	2.60		2.60	0.7 ~ 3.8	790	170 ~ 1210	3.29	A	395	3.65	-	-	-	-	
	2.0	2.0	3.20		3.20	0.7 ~ 4.8	950	170 ~ 1510	3.37	A	475	4.40	-	-	-	-	
	2.5	2.5	3.60		3.60	0.7 ~ 5.5	1130	170 ~ 1800	3.19	B	565	5.25	-	-	-	-	
	3.5	3.5	4.50		4.50	0.7 ~ 6.2	1350	170 ~ 1910	3.33	B	675	6.25	-	-	-	-	
	4.2	4.2	5.00		5.00	1.1 ~ 6.4	1650	210 ~ 2280	3.03	C	825	7.65	-	-	-	-	
	5.0	5.0	5.30		5.30	1.1 ~ 6.8	1740	210 ~ 2390	3.05	C	870	8.05	-	-	-	-	
2 Room	1.6 + 1.6	3.2	2.60	2.60	5.20	1.1 ~ 7.0	1330	210 ~ 2010	3.91	A	665	6.00	3.80	3.80	A	1400	
	1.6 + 2.0	3.6	2.40	3.00	5.40	1.1 ~ 7.0	1380	210 ~ 1990	3.91	A	690	6.25	4.00	3.80	A	1474	
	1.6 + 2.5	4.1	2.10	3.30	5.40	1.1 ~ 7.0	1380	210 ~ 1990	3.91	A	690	6.25	4.00	3.80	A	1474	
	1.6 + 3.5	5.1	1.70	3.70	5.40	1.1 ~ 7.0	1380	210 ~ 1990	3.91	A	690	6.25	4.00	3.80	A	1474	
	1.6 + 4.2	5.8	1.55	4.05	5.60	1.1 ~ 7.2	1410	210 ~ 2000	3.97	A	705	6.40	4.20	3.80	A	1547	
	1.6 + 5.0	6.6	1.35	4.25	5.60	1.1 ~ 7.2	1410	210 ~ 2000	3.97	A	705	6.40	4.20	3.80	A	1547	
	2.0 + 2.0	4.0	2.70	2.70	5.40	1.1 ~ 7.0	1370	210 ~ 1970	3.94	A	685	6.20	4.00	3.80	A	1474	
	2.0 + 2.5	4.5	2.40	3.00	5.40	1.1 ~ 7.0	1370	210 ~ 1970	3.94	A	685	6.20	4.00	3.80	A	1474	
	2.0 + 3.5	5.5	2.05	3.55	5.60	1.1 ~ 7.2	1410	210 ~ 2000	3.97	A	705	6.40	4.20	3.80	A	1547	
	2.0 + 4.2	6.2	1.80	3.80	5.60	1.1 ~ 7.2	1410	210 ~ 2000	3.97	A	705	6.40	4.20	3.80	A	1547	
	2.0 + 5.0	7.0	1.60	4.00	5.60	1.1 ~ 7.2	1410	210 ~ 2000	3.97	A	705	6.40	4.20	3.80	A	1547	
	2.5 + 2.5	5.0	2.80	2.80	5.60	1.1 ~ 7.2	1410	210 ~ 2000	3.97	A	705	6.40	4.20	3.80	A	1547	
	2.5 + 3.5	6.0	2.35	3.25	5.60	1.1 ~ 7.2	1410	210 ~ 2000	3.97	A	705	6.40	4.20	3.80	A	1547	
	2.5 + 4.2	6.7	2.10	3.50	5.60	1.1 ~ 7.2	1410	210 ~ 2000	3.97	A	705	6.40	4.20	3.80	A	1547	
	2.5 + 5.0	7.5	1.85	3.75	5.60	1.1 ~ 7.2	1410	210 ~ 2000	3.97	A	705	6.40	4.20	3.80	A	1547	
3.5 + 3.5	7.0	2.80	2.80	5.60	1.1 ~ 7.2	1410	210 ~ 2000	3.97	A	705	6.40	4.20	3.80	A	1547		
3.5 + 4.2	7.7	2.55	3.05	5.60	1.1 ~ 7.2	1410	210 ~ 2000	3.97	A	705	6.40	4.20	3.80	A	1547		